

Model No.: SV-8C-GP Made in USA Manifold Valve

Thank you for Purchasing the SV-8 by Slam Specialties

This instruction sheet provides mounting dimensions and wiring color codes to simplify your installation of the valve. If you have any questions or concerns, please call 888-352-5225 or e-mail info@slamspecialties.com

Product Contents:

- (1) SV-8 manifold valve
- (1) Wire harness
- (4) 1" 10-24 Stainless screws
- (4) 10-24 Stainless nylock nuts
- (8) Stainless washers
- (1) Red ring terminal
- (4) 1/8" NPT hex plugs
- (1) 3/8" Port plug



Only one inlet/tank port is required for valve to operate. (See Recommendations below)

The second inlet can be plugged with the included port plug.

Technical date:		
200 PSI Max operating pressure		
(6) 3/8 Push-to-Connect fittings		
(4) 1/8 NPT Gauge Ports w/hex plugs		
Anodized 6061-T6 Aluminum manifold		
Dual Slot exhaust ports w/mufflers		
Steel internal operators		
(8) 13w 12v DC Solenoid Coils		



- 1.) Up 1 —— Black
- 2.) Up 2 —— Yellow
- 3.) Up 3 —— Brown 4.) Up 4 —— Purple
- 5.) Down 1 Green
- 6.) Down 2 Orange
- 7.) Down 3 Blue
- 8.) Down 4 White

Wiring		
Port	Function	Wire Color
1	Fill	Black
	Exhaust	Green
2	Fill	Yellow
	Exhaust	Orange
3	Fill	Brown
	Exhaust	Blue
4	Fill	Purple
	Exhaust	White
GROUND		Black w/ Ring Terminal

Harness wiring information


The SV-8 includes a short wiring harness that will plug into the connector on the valve wire that allows you to use any control system. The functions are color coded to the wire chart above.

Recommendations:

Water traps/Air filter are recommended between the air tank and the valve. One water trap/filter per inlet. If you are using one tank port on the valve, only one water trap/filter in necessary. Water trap/filter will help to prevent debris from the air system from entering the valve which could potentially cause the valve to not close fully.



Model No.: SV-8C-GP Made in USA Manifold Valve



Mounting Bracket template

